

PACER

SERIES 'S' SELF-PRIMING CENTRIFUGAL PUMPS

HORIZONTAL . . . LONG or CLOSE COUPLED
for industrial, agricultural and marine use

**CLOSE-COUPLED
ELECTRIC**



GASOLINE ENGINE

**PEDESTAL MOUNTED
for flexible coupling**



HYDRAULIC

PNEUMATIC



LONG COUPLED

• **CHOICE OF MATERIALS -**

Glass reinforced — polyester, polypropylene or Ryton® EPDM, Buna-N or Viton® elastomers, and stainless steel or non-metallic fasteners for resistance from chemical attack

(See Chemical Resistance Chart)

• **FLOW RATES (electric driven)**

To 280 U.S. GPM or 120 ft. TDH @ 60 Hz
(To 883 LPM or 25.4m TDH @ 50 Hz)

• **FLOW RATES (Engine driven)**

To 290 U.S. GPM or 126 ft. TDH
(To 1060 LPM or 38.4m TDH)

• **Suction lift to 25 ft. (7.6m) VERTICAL***

• **1-1/2", 2" or 3" NPT ports. All polyester and 2" polypropylene also available with BSP threads.**

• **ELECTRIC MOTOR, GASOLINE ENGINE, DIESEL ENGINE, HYDRAULIC or PNEUMATIC DRIVEN**

• **CLOSE-COUPLED, LONG-COUPLED or PEDESTAL MOUNTED**

• **BUILT-IN CHECK VALVE FOR QUICK PRIMING**

* Based on water-like liquids at 70°F and at 3450 RPM after initial priming of pump housing.



AQUACULTURE



AGRICULTURE



MARINE



IRRIGATION AND
SOLUTION TRANSFER



OIL FIELD



INDUSTRIAL AND
WASTE TREATMENT



CHEMICAL
APPLICATIONS



SPRAY RIG